

SW2021

Hot/Cold Water Cleaner



Specifications

- ⇒ 3000 P.S.I. (200 Bar) pump pressure
- ⇒ 4200 P.S.I. turbo pressure (optional)
- ⇒ 21 Litres Per Minute pump volume
- ⇒ 415 Volt 10 H.P. electric motor
- ⇒ 1450 RPM low speed pump
- ⇒ 20 amp plug 3 phase
- ⇒ Temperatures up to 90°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High & Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Bypass shutdown timer
- ⇒ Operators and parts manuals

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis	Resistant to corrosion
Adjustable thermostat for hot water temperature control	Set the ideal temperature for any application
Bypass shutdown timer	Increases life of the machine by shutting down when not in use

For more information,
please visit our website

spitwater.com.au